

RJ45 Heavy Duty male 90° up IDC

8-pol., AWG23-22, 5- 9mm, shielded, CAT5

Ethernet
PROFINET

Male 90°

90° on top

RJ45, 8-pole

Field-wireable




shielded

Protection IP20

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Länk till produkt](#)

Illustration



Produkten kan skilja sig från bilden



Side 1

Family construction form

RJ45

Material contact	Copper alloy
No. of poles	8
Kommersiella uppgifter	
ECLASS-6.0	27260705
ECLASS-6.1	27260703
ECLASS-7.0	2744010
ECLASS-8.0	2744010
ECLASS-9.0	27440114
ECLASS-10.1	2744010
ECLASS-11.1	2744010
ECLASS-12.0	27440114
ETIM-5.0	EC002635
Förpackningsenhet	1
GTIN	4048879671088
Kundens tullnummer	85366990
Electrical data Supply	
Operating voltage AC	50 V
Operating voltage DC	50 V
Operating current max.	1,75 A
Industrial communication	
Transfer parameters	CAT5e (ANSI/TIA/EIA-568-B.2-2001), CAT5 Class D according to ISO/IEC 11801
Data transmission rate max.	1000 MBit/s
Installation	
Connection cross section min.	0,23 mm ²
Connection cross section max.	0,32 mm ²
AWG number min.	23
AWG number max.	22
Installation Connection	
Connection	Cut clamps IDC
Mating cycles min.	750
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP20
Overvoltage category (EN 60950-1)	I
Mechanical data Material data	
Coating housing	nickel plated
Coating contact	gold plated
Material housing	Zinc die-casting
Material contact carrier	PC
Mechanical data Mounting data	
Clamping range min.	5 mm
Clamping range max.	9 mm
Environmental characteristics Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	70 °C