MURR ELEKTRONIK
stay connected

## RMME 11/230 AC INPUT RELAY


IN: 230 VAC/DC - OUT: 125 VAC/DC / 1 A


1 relay; 1 NO contact
1 A
230 V AC
Screw terminals

Länk till produkt

### Illustration






Produkten kan skilja sig från bilden

### Kommersiella uppgifter

| | |
|---|---|
| ECLASS-6.0 | 27371001 |
| ECLASS-6.1 | 27371601 |
| ECLASS-7.0 | 27371601 |
| ECLASS-8.0 | 27371601 |
| ECLASS-9.0 | 27371601 |
| ECLASS-10.1 | 27371601 |

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27371601 |
| ECLASS-12.0 | 27371601 |
| ETIM-5.0 | EC001437 |
| Förpackningsenhet | 1 |
| GTIN | 4048879027540 |
| Kundens tullnummer | 85364900 |
| **Electrical data \| Input** | |
| Input voltage AC | 230 V |
| Input voltage AC min. | 195 V |
| Input voltage AC max. | 253 V |
| Input voltage DC | 230 V |
| Input voltage DC min. | 195 V |
| Input voltage DC max. | 253 V |
| Input current | 6 mA |
| **Electrical data \| Output** | |
| Utilization category AC-15 (EN IEC 60947-5-1) | 0,25 A @ 50 V |
| Switching frequency max. | 15 Hz |
| Power rating AC max. | 60 VA |
| Power rating DC max. | 30 W |
| Switching voltage AC max. | 125 V |
| Switching voltage DC max. | 125 V |
| Switching current DC | 1 mA |
| Switching current max. | 1 A |
| Switching capacity AC-12 (EN IEC 60947-5-1) | 0.5 A (50 V AC) |
| **Diagnostics** | |
| Status indication LED | yellow |
| **Device protection** | |
| Condition lifetime | load-dependent |
| **Device protection \| Electrical** | |
| Rated surge voltage | 1,5 kV |
| Electrical lifetime | 100000000 Cycles |
| **Device protection \| Mechanical** | |
| Mechanical endurance | 100000000 Cycles |
| **Mechanical data** | |
| Drop-out time max. | 10 ms |
| Response time max. | 10 ms |
| Bounce time max. | 1 ms |
| **Mechanical data \| Material data** | |
| Material contact | Pd Ni-Au Rh |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, G32, (EN 60715) |
| Height | 56 mm |
| Width | 12 mm |
| Depth | 64 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| **Connection type 2** | |

| | |
|---|---|
| Connection type 1 | X1 |
| Connection type 2 | X2 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 2 |
| PIN 1 | A 1 |
| PIN 2 | A 2 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 2 |
| PIN 1 | 13 |
| PIN 2 | 14 |