



## RMM 11/24VDC WITH GROUND BRIDGE OUTPUT RELAY

IN: 24 VAC/DC - OUT: 250 VAC/DC / 5 A

1 relay; 1 NO contact  
5 A  
24 V AC/DC  
with minus plug link  
Screw terminals

### Länk till produkt

#### Illustration



Produkten kan skilja sig från bilden



#### General product information

Scope of delivery Jumper (Art-No. 90960)

#### Kommersiella uppgifter

|            |          |
|------------|----------|
| ECLASS-6.0 | 27371001 |
| ECLASS-6.1 | 27371601 |
| ECLASS-7.0 | 27371601 |

|                    |               |
|--------------------|---------------|
| ECLASS-8.0         | 27371601      |
| ECLASS-9.0         | 27371601      |
| ECLASS-10.1        | 27371601      |
| ECLASS-11.1        | 27371601      |
| ECLASS-12.0        | 27371601      |
| ETIM-5.0           | EC001437      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879027342 |
| Kundens tullnummer | 85364900      |

**Electrical data | Input**

|                       |        |
|-----------------------|--------|
| Input voltage AC      | 24 V   |
| Input voltage AC min. | 19,2 V |
| Input voltage AC max. | 30 V   |
| Input voltage DC      | 24 V   |
| Input voltage DC min. | 19,2 V |
| Input voltage DC max. | 30 V   |
| Input current         | 15 mA  |

**Electrical data | Output**

|                                               |                                             |
|-----------------------------------------------|---------------------------------------------|
| Utilization category AC-15 (EN IEC 60947-5-1) | 3 A @ 24 V, 3 A @ 110 V, 3 A @ 230 V        |
| Utilization category DC-13 (EN IEC 60947-5-1) | 1,5 A @ 24 V, 0,3 A @ 110 V, 0,15 A @ 230 V |
| Switching frequency max.                      | 10 Hz                                       |
| Power rating AC max.                          | 1250 VA                                     |
| Power rating DC max.                          | 240 W                                       |
| Switching voltage AC max.                     | 250 V                                       |
| Switching voltage DC max.                     | 250 V                                       |
| Switching current DC                          | 100 mA                                      |
| Switching current max.                        | 5 A                                         |
| Switching capacity AC-12 (EN IEC 60947-5-1)   | 5 A (24/110/230 V AC)                       |

**Diagnostics**

|                       |     |
|-----------------------|-----|
| Status indication LED | red |
|-----------------------|-----|

**Device protection**

|                    |                |
|--------------------|----------------|
| Condition lifetime | load-dependent |
|--------------------|----------------|

**Device protection | Electrical**

|                     |                 |
|---------------------|-----------------|
| Rated surge voltage | 4 kV            |
| Electrical lifetime | 10000000 Cycles |

**Device protection | Mechanical**

|                      |                 |
|----------------------|-----------------|
| Mechanical endurance | 10000000 Cycles |
|----------------------|-----------------|

**Mechanical data**

|                    |        |
|--------------------|--------|
| Drop-out time max. | 15 ms  |
| Response time max. | 10 ms  |
| Bounce time max.   | 1,5 ms |

**Mechanical data | Material data**

|                  |               |
|------------------|---------------|
| Material contact | Ag Ni 0.15 hv |
|------------------|---------------|

**Mechanical data | Mounting data**

|                            |                                     |
|----------------------------|-------------------------------------|
| Mounting method            | geschnappt                          |
| Suitable for mounting type | Mounting rail TH35, G32, (EN 60715) |
| Height                     | 56 mm                               |
| Width                      | 12 mm                               |
| Depth                      | 65 mm                               |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -25 °C |
| Operating temperature max. | 60 °C  |
| Storage temperature min.   | -40 °C |
| Storage temperature max.   | 80 °C  |

**Connection type 2**

|                          |                    |
|--------------------------|--------------------|
| Connection type 1        | X1                 |
| Connection type 2        | X2                 |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 2                  |
| PIN 1                    | A 2                |
| PIN 2                    | A 1                |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 2                  |
| PIN 1                    | 13                 |
| PIN 2                    | 14                 |