MURR ELEKTRONIK
stay connected

**Adaptor M12 Male / M12 Female**


Buffer module for DI (Pin 1-3)


Adapter
Male - female
M12 – M12, 4-pole
max. 700 mA
94 µF

## Länk till produkt

### Illustration






Produkten kan skilja sig från bilden

### Kommersiella uppgifter

| | |
|---|---|
| ECLASS-6.0 | 27143423 |
| ECLASS-6.1 | 27260702 |
| ECLASS-7.0 | 27440102 |
| ECLASS-8.0 | 27440102 |
| ECLASS-9.0 | 27440102 |

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-10.1 | 27440102 |
| ECLASS-11.1 | 27440102 |
| ECLASS-12.0 | 27440106 |
| ETIM-5.0 | EC001855 |
| Förpackningsenhet | 1 |
| GTIN | 4048879713467 |
| Kundens tullnummer | 85322100 |
| **Electrical data \| Supply** | |
| Operating voltage DC | 24 V |
| Operating voltage DC min. | 18 V |
| Operating voltage DC max. | 30,2 V |
| Total current max. | 0,7 A |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP67 |
| Additional condition protection degree | screwed, mounted |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -30 °C |
| Operating temperature max. | 70 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 85 °C |
| Relative humidity max. (operation) | 85 % |
| **Conformity** | |
| Product standard | EN 61131-2 |