

MASI68 I/O MODUL

2 digital inputs and 2 digital outputs

Compact module

DI2 - 0.1 A DO2 - 0.5 A (C) - 4× M8 (AB)


Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

24 V DC external (18...30.2 V DC) EN 61131-2

Länk till produkt**Illustration**

Produkten kan skilja sig från bilden

**Kommersiella uppgifter**

ECLASS-6.0	27242604
ECLASS-7.0	27242604
ECLASS-8.0	27242604
ECLASS-9.0	27242604
ETIM-5.0	EC001599
Förpackningsenhet	1
GTIN	4048879373524
Kundens tullnummer	85176200

Electrical data | Supply

Bus voltage AS-Interface DC min.	26,5 V
Bus voltage AS-Interface DC max.	31,6 V
Current consumption AS-i port max.	250 mA
Total current max.	1,5 A

Electrical data | Input

Overload resistant	yes
Short-circuit protected	yes
Type input	PNP, for 3-wire sensors or mechanical switches
Current carrying capacity max.	0,1 A

Electrical data | Output

Overload resistant	yes
--------------------	-----

Short-circuit protected	yes
-------------------------	-----

Output current per pin max.	0,5 A
-----------------------------	-------

Industrial communication | Bus data

Address setting type	M12 connection and programming device, Master
----------------------	---

Slave address range	(0), 1 A...31 A, 1 B...31 B
---------------------	-----------------------------

Industrial communication | AS-Interface

Profile (IO.ID.ID2)	S-7.A.E
---------------------	---------

Diagnostics

Diagnostic	No voltage
------------	------------

Diagnostic via LED	per module
--------------------	------------

LED display	Ethernet connection/data traffic
-------------	----------------------------------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP68
-------------------------------------	------

Mechanical data | Mounting data

Mounting method	screwed
-----------------	---------

Height	85 mm
--------	-------

Width	30 mm
-------	-------

Depth	34,5 mm
-------	---------

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
----------------------------	--------

Operating temperature max.	60 °C
----------------------------	-------

Storage temperature min.	-20 °C
--------------------------	--------

Storage temperature max.	70 °C
--------------------------	-------

Connection type 3

Connection type 1	A C
-------------------	-----

Connection type 2	AUX
-------------------	-----

Connection type 3	B D
-------------------	-----

Family construction form	M8
--------------------------	----

Gender	female
--------	--------

Color contact carrier	black
-----------------------	-------

Coding	A
--------	---

No. of poles	3
--------------	---

PIN 1	Usens +
-------	---------

PIN 3	Usens -
-------	---------

PIN 4	DI
-------	----

Family construction form	M12
--------------------------	-----

Gender	male
--------	------

Color contact carrier	black
-----------------------	-------

Coding	A
--------	---

No. of poles	4
--------------	---

PIN 1	AS-i +
-------	--------

PIN 2	0 V AUX POWER
-------	---------------

PIN 3	AS-i -
-------	--------

PIN 4	24 V DC AUX POWER
-------	-------------------

Family construction form	M8
--------------------------	----

Gender	female
--------	--------

Color contact carrier	black
-----------------------	-------

Coding	A
--------	---

No. of poles	3
--------------	---

PIN 1	n.c.
-------	------

PIN 3	0 V
PIN 4	DO
