MURR ELEKTRONIK
stay connected

Gateway EtherCAT/AS-i, 2 Masters


Product discontinued since 2023-02-13

Gateway-Singlemaster
via pluggable spring clamp plug-in terminals on the front 0.5...1.5 mm²
AS-Interface/PROFIBUS DP
Specification 3.0
Current manuals, GSD/type data can be downloaded at: www.murrelektronik.com
Other gateways on request.

Länk till produkt

Illustration





Produkten kan skilja sig från bilden

Kommersiella uppgifter	
ECLASS-6.0	27242608
ECLASS-6.1	27242608
ECLASS-7.0	27242608
ECLASS-8.0	27242608
ECLASS-9.0	27242608
ECLASS-10.1	27242608
ECLASS-11.1	27242608
ECLASS-12.0	27242608
ETIM-5.0	EC001604
Förpackningsenhet	1
GTIN	4048879444712
Kundens tullnummer	85176200
Electrical data	
Rated operating current AS-Interface max.	70 mA
Electrical data | Supply	
Operating voltage DC	30 V
Industrial communication | Bus data	
Automatic baudrate detection	yes

Baud rate min.	9,6 kBaud
Baud rate max.	12 MBaud
Industrial communication | AS-Interface	
AS-i specification	V3.0
Number of slaves max.	62
Diagnostic interface serial	PS2/RS232
Cycle time AS-i	150 µs × (number of slaves + 2)
Industrial communication | Profibus	
PROFIBUS function	Illustration of AS-Interface slaves as I/O process data in PROFIBUS DP, full diagnostic configuration via DP-master
Installation | Connection	
Family construction form	SUB-D9
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP20
Rated insulation voltage	500 V
Short-circuit protected	yes
Overload resistant	yes
Mechanical data	
Number of operating buttons	4
Function operating buttons	ESC, Mode, OK, Set
Mechanical data | Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	120 mm
Width	75 mm
Depth	70 mm
Environmental characteristics | Climatic	
Operating temperature min.	0 °C
Operating temperature max.	55 °C
Storage temperature min.	-20 °C
Storage temperature max.	85 °C
Conformities, approvals	
Low Voltage Directive	EN 50295