MURR ELEKTRONIK
stay connected

MIRO BT


IP65 Bluetooth Master/Slave PROFINET

PROFINET
Bluetooth Master/Slave
100 Mbit/s
Connection cables are in the online shop under "Connection Technology".

Länk till produkt

Illustration





Produkten kan skilja sig från bilden

Kommersiella uppgifter

ECLASS-6.0	19170101
ECLASS-6.1	27242602
ECLASS-7.0	27242602
ECLASS-8.0	27242602
ECLASS-9.0	27242602
ECLASS-10.1	27242602
ECLASS-11.1	27242602
ECLASS-12.0	27242602
ETIM-5.0	EC001604
ETIM-6.0	EC001604
ETIM-7.0	EC001604
Förpackningsenhet	1
GTIN	4048879582414
Kundens tullnummer	85176200

Electrical data | Supply

Operating voltage DC	24 V
Operating current max.	150 mA

Industrial communication

Radio frequency	2.4 GHz Bluetooth
Transmission power	100 mW

MURR ELEKTRONIK
stay connected

Installation | Connection	
Antenna connection	SMA-female (50 Ω)
Mounting set	M4
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Mechanical data | Material data	
Color housing	black
Material housing	Metal
Mechanical data | Mounting data	
Mounting method	screwed
Height	125 mm
Width	86 mm
Depth	41 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Storage temperature min.	-40 °C
Storage temperature max.	75 °C
Conformity	
Product standard	EN 61131-2
Connection type 4	
Connection type 1	10M / 100M
Connection type 2	24 V DC
Connection type 3	Ant
Family construction form	M12
Gender	female
Color contact carrier	green
Coding	D
No. of poles	4
PIN 1	TD +
PIN 2	RD +
PIN 3	TD -
PIN 4	RD -
Family construction form	M12
Gender	male
Color contact carrier	black
Coding	A
No. of poles	5
PIN 1	25 V DC
PIN 3	0 V
PIN 5	PE
Family construction form	SMA
Gender	female
No. of poles	2
PIN 1	Signal
PIN 2	PE
Family construction form	USB Mini
Gender	female
No. of poles	5