stay connected

MKS - D 10/1300 - 1 DIODE MODULES


Mounting rail / screw-type terminal


Universal diode 1 300 V, 1 A
10 diodes
separation contact via pluggable jumpers
Diode modules are suitable for the suppression of inductive loads (valve, contactor, etc.)

Länk till produkt

Illustration







Produkten kan skilja sig från bilden

Kommersiella uppgifter

ECLASS-6.0	27371010
ECLASS-6.1	27371010
ECLASS-7.0	27371010
ECLASS-8.0	27371010
ECLASS-9.0	27371010
ECLASS-10.1	27371010

MURR ELEKTRONIK
stay connected

ECLASS-11.1	27371010
ECLASS-12.0	27371010
ETIM-5.0	EC002780
Förpackningsenhet	1
GTIN	4048879041874
Kundens tullnummer	85411000
Electrical data | Supply	
Operating voltage AC max.	48 V
Operating voltage DC max.	48 V
Mechanical data | Mounting data	
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, G32, (EN 60715)
Height	86 mm
Width	45 mm
Depth	62 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Connection type 1	
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
No. of poles	20