MURR ELEKTRONIK
stay connected

## ASSEMBLY MODULE MKS - M 8


Mounting rail / screw-type terminal


8 pairs of solder pins
screw terminals connected to solder pin pairs

[Länk till produkt]

### Illustration






Produkten kan skilja sig från bilden

### Kommersiella uppgifter

| | |
|---|---|
| ECLASS-6.0 | 27379201 |
| ECLASS-6.1 | 27141149 |
| ECLASS-7.0 | 27141149 |
| ECLASS-8.0 | 27141149 |
| ECLASS-9.0 | 27141149 |
| ECLASS-10.1 | 27141149 |
| ECLASS-11.1 | 27141149 |
| ECLASS-12.0 | 27141149 |

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ETIM-5.0 | EC002780 |
| Förpackningsenhet | 1 |
| GTIN | 4048879041805 |
| Kundens tullnummer | 85369010 |
| **Electrical data \| Supply** | |
| Operating voltage AC max. | 250 V |
| Operating voltage DC max. | 250 V |
| Operating current max. | 5 A |
| **Device protection \| Media** | |
| Flame resistance | flame retardant |
| **Mechanical data \| Material data** | |
| Housing properties | removable cover |
| Material housing | Plastic |
| **Mechanical data \| Mounting data** | |
| Distance of solder pins | 40 mm |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, G32, (EN 60715) |
| Height | 86 mm |
| Width | 45 mm |
| Depth | 62 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| **Connection type 1** | |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| No. of poles | 16 |