MURR ELEKTRONIK
stay connected

HYBRID FIELD-BUS COUPLERS


Conversion electrical-electrical (passive)

CU, CU (female/male)
Han-Brid ® a registered trademark of HARTING KGaA.

Länk till produkt

Illustration





Produkten kan skilja sig från bilden

Kommersiella uppgifter	
ECLASS-6.0	27189217
ECLASS-7.0	27189217
ECLASS-8.0	27189217
ECLASS-9.0	27189217
ETIM-5.0	EC002641
Förpackningsenhet	1
GTIN	4048879041485
Kundens tullnummer	85366990
Electrical data | Supply	
Operating voltage DC	24 V
Industrial communication	
Data transmission rate max.	12 MBit/s
Installation	
Connection cross-section solid max.	0,25 mm²
Connection cross-section stranded/fine-stranded max.	2,5 mm²
Installation | Connection	
Connection	Spring clamp plug-in terminals
Device protection	
Shielded	no
Device protection | Media	
Flame resistance	flame retardant
Mechanical data | Material data	
Color housing	black
Material housing	Plastic

Mechanical data | Mounting data	
Height cutout	90 mm
Width cutout	80 mm
Height	103 mm
Width	93 mm
Depth	65 mm
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	50 °C