MURR ELEKTRONIK
stay connected

Reset button with 2 illuminated push buttons


Every 1 NO contact in a IP65 enclosure


R-Button / 42 2NO L M12(8)
with M12 connection
8-pole
2 buttons can be lit (each 1 NO contact)
Delivery contents:
Flat lens, transparent clear, red, yellow, green, blue
Label plates, O, I, R, ↑,↓
mounting with clip on the back side


Länk till produkt

Illustration









Produkten kan skilja sig från bilden

Kommersiella uppgifter

ECLASS-6.0	27371228
ECLASS-6.1	27371228

MURR ELEKTRONIK
stay connected

ECLASS-7.0	27371228
ECLASS-8.0	27371228
ECLASS-9.0	27371228
ECLASS-10.1	27371228
ECLASS-11.1	27371228
ECLASS-12.0	27371228
ETIM-5.0	EC000225
Förpackningsenhet	1
GTIN	4048879594325
Kundens tullnummer	85365080
Electrical data	
Operating voltage AC/DC LED illumination max.	30 V
Operating current LED illumination	14 mA @24 V DC
Electrical data | Supply	
Operating voltage DC min.	1 V
Operating voltage DC max.	36 V
Operating voltage DC (UL Recognized)	30 V
Operating current	1,5 A
Device protection	
Condition lifetime	load-dependent, temperature dependent
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Electrical lifetime	1000000 Cycles
Device protection | Mechanical	
Mechanical endurance	1000000 Cycles
Mechanical data	
Bounce time max.	10 ms
Mechanical data | Material data	
Material contact	AgNi
Mechanical data | Mounting data	
Height	29 mm
Width	124 mm
Depth	42 mm
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	70 °C
Storage temperature min.	-25 °C
Storage temperature max.	85 °C
Connection type 1	
Family construction form	M12
Gender	male
Color contact carrier	black
Coding	A
No. of poles	8
PIN 1	NO 1
PIN 2	NO 1
PIN 3	X 2 -
PIN 4	X 1 +
PIN 5	NO 2

PIN 6	NO 2
PIN 7	X 2 -
PIN 8	X 1 +