MURR ELEKTRONIK
stay connected

LED - LT 24/RED

(red)
24 V DC
with lamp test input
The modules are suitable for wall thickness of 1.5...5.0 mm.

Länk till produkt

Illustration



Produkten kan skilja sig från bilden

Kommersiella uppgifter	
ECLASS-6.0	27261590
ECLASS-6.1	27261501
ECLASS-7.0	27261501
ECLASS-8.0	27261501
ECLASS-9.0	27261501
ECLASS-10.1	27261501
ECLASS-11.1	27261501
ECLASS-12.0	27261501
ETIM-5.0	EC000272
Förpackningsenhet	10
GTIN	4048879041249
Kundens tullnummer	85318070
Electrical data | Supply	
Operating voltage DC	24 V
Operating voltage DC min.	20,4 V
Operating voltage DC max.	26,4 V
Current consumption max.	10 mA
Installation | Connection	
Connection information	Faston 2.8×0.8 mm
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Device protection | Media	
Flame resistance	flame retardant
Mechanical data	
Diameter LED	5 mm

Mechanical data | Material data	
Material housing	Plastic
Mechanical data | Mounting data	
Diameter front panel drilling	9 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	50 °C