MURR ELEKTRONIK
stay connected

## MET 1-PHASE CONTROL AND ISOLATION TRANSFORMER


P: 2000VA IN: 400VAC+/- 5% OUT: 230VAC


Single-phase - Control and Isolation Transformers
2000 VA
Isolation class T 40/B

Länk till produkt

### Illustration






Produkten kan skilja sig från bilden

### Kommersiella uppgifter

| | |
|---|---|
| ECLASS-6.0 | 27031302 |
| ECLASS-6.1 | 27031302 |
| ECLASS-7.0 | 27031302 |
| ECLASS-8.0 | 27031302 |
| ECLASS-9.0 | 27031302 |
| ECLASS-10.1 | 27031302 |
| ECLASS-11.1 | 27031302 |

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-12.0 | 27031302 |
| ETIM-5.0 | EC002486 |
| Förpackningsenhet | 1 |
| GTIN | 4048879078825 |
| Kundens tullnummer | 85043200 |
| **Electrical data \| Supply** | |
| Power frequency | 50 ... 60 Hz |
| **Electrical data \| Input** | |
| Input voltage AC | 400 V |
| Input voltage AC min. | 380 V |
| Input voltage AC max. | 420 V |
| Current input AC | 5,1 A |
| Max. inrush current | 76 A |
| Short-circuit current | 182 A |
| **Electrical data \| Output** | |
| Output voltage AC | 230 V |
| Output voltage adjustable | no |
| Power rating AC max. | 2000 VA |
| **Device protection \| Electrical** | |
| Insulation test voltage input - output | 4 kV |
| **Mechanical data \| Mounting data** | |
| Suitable for mounting type | Long-hole mounting |
| Mounting dimension a | 200 mm |
| Mounting dimension b | 174 mm |
| Mounting dimension c | 9 mm |
| Height | 170 mm |
| Width | 195 mm |
| Depth | 250 mm |
| Diameter bore | 9 mm |
| Length bore | 14 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 40 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 80 °C |
| **Conformity** | |
| Product standard | EN 61558-1, EN 61558-2-4, EN 62041 category 0 |