

**MVP12, 8XM12, 4POLE, PLUGGABLE CABLE**

5.0m PUR/PVC 16x0,34+5x0,75, w/o LED's

8-way, 5-pole



PUR/PVC

5.0 m

Potential separation as option

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

**Länk till produkt****Illustration**

Produkten kan skilja sig från bilden

**Kommersiella uppgifter**

|            |          |
|------------|----------|
| ECLASS-6.0 | 27279219 |
| ECLASS-6.1 | 27279219 |
| ECLASS-7.0 | 27279219 |

|                    |               |
|--------------------|---------------|
| ECLASS-8.0         | 27279219      |
| ECLASS-9.0         | 27440108      |
| ECLASS-10.1        | 27440108      |
| ECLASS-11.1        | 27440108      |
| ECLASS-12.0        | 27440108      |
| ETIM-5.0           | EC002585      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879061636 |
| Kundens tullnummer | 85369010      |

**Electrical data | Supply**

|                                               |      |
|-----------------------------------------------|------|
| Operating voltage DC                          | 24 V |
| Current operating per contact max.            | 4 A  |
| Total current at 1 time current feed-in max.  | 8 A  |
| Total current at 2 times current feed-in max. | 16 A |

**Industrial communication**

|                            |   |
|----------------------------|---|
| Number of signals per port | 2 |
|----------------------------|---|

**Installation | Connection**

|              |         |
|--------------|---------|
| Mounting set | M12 x 1 |
|--------------|---------|

**Device protection | Electrical**

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP67             |
| Additional condition protection degree | screwed, mounted |

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

**Mechanical data | Mounting data**

|                 |                |
|-----------------|----------------|
| Mounting method | Schraubgewinde |
| Height          | 149,2 mm       |
| Width           | 50,2 mm        |
| Depth           | 17,2 mm        |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 80 °C  |

**Installation | Cable**

|                                   |                                                                                                                             |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| STOOW style jacket                | Hybrid, Signal, Power                                                                                                       |
| Cable identification              | 374                                                                                                                         |
| Cable Type                        | 2                                                                                                                           |
| Jacket Color                      | gray                                                                                                                        |
| Type of Certificate               | cURus                                                                                                                       |
| Amount stranding                  | 1                                                                                                                           |
| Stranding                         | 4 wires twisted                                                                                                             |
| Amount stranding (type 2)         | 1                                                                                                                           |
| Stranding (type 2)                | 9 wires around Stranding combination twisted                                                                                |
| wire arrangement                  | gray-pink, white, red-blue, green, (green-yellow, brown 1, blue 1, brown 2, blue 2, green-white, yellow, brown-green, gray) |
| Cable weight                      | 140,94 g/m                                                                                                                  |
| Material jacket                   | PUR                                                                                                                         |
| Shore hardness jacket             | 87 ± 5 Shore A                                                                                                              |
| Freedom from ingredients (jacket) | lead-free, cadmium-free, CFC-free, silicone-free                                                                            |
| Outer-diameter (jacket)           | 9,2 mm                                                                                                                      |
| Tolerance outer diameter (sheath) | ± 5 %                                                                                                                       |

|                                                   |                                                      |
|---------------------------------------------------|------------------------------------------------------|
| Material inner jacket                             | PVC                                                  |
| Color (inner jacket)                              | gray                                                 |
| Material wire insulation                          | PVC                                                  |
| Amount wires                                      | 8                                                    |
| Outer diameter insulation                         | 1,3 mm                                               |
| Outer diameter tolerance core insulation          | ± 5 %                                                |
| Shore hardness wire insulation                    | 43 ± 5 Shore D                                       |
| Material properties wire insulation               | good machinability                                   |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, silicone-free     |
| Amount strands (wire)                             | 19                                                   |
| Diameter of single wires                          | 0,15 mm                                              |
| Conductor crosssection (wire)                     | 0,34 mm²                                             |
| Traversing distance (C-track)                     | 5 m @ 25 °C   horizontal                             |
| Material conductor wire                           | Stranded copper wire, bare                           |
| Conductor type (wire)                             | Strand class 5                                       |
| Travel speed (C-track)                            | 5                                                    |
| Material wire insulation (Power)                  | PVC                                                  |
| Outer diameter wire insulation (Power)            | 1,8 mm                                               |
| Tolerance outer diameter wire insulation (Power)  | ±5 %                                                 |
| Shore hardness wire insulation (Power)            | 43±5 Shore D                                         |
| Material properties wire insulation (Power)       | good machinability                                   |
| Ingredient freeness wire insulation (Power)       | lead-free, cadmium-free, CFC-free, silicone-free     |
| Printing colour wire insulation (Power)           | white (isolation blue), white (isolation brown)      |
| Amount strands wire (Power)                       | 42                                                   |
| Diameter of single wires (Power)                  | 0,15 mm                                              |
| Wire conductor cross section (Power)              | 0,75 mm²                                             |
| Material conductor wire (Power)                   | Stranded copper wire, bare                           |
| Conductor type wire (Power)                       | strand class 6                                       |
| Max. rated voltage (conductor - conductor)        | 300 V                                                |
| Max. rated voltage (conductor - ground)           | 300 V                                                |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                    |
| Current load capacity min. wire                   | 4 A                                                  |
| Loop resistance                                   | 7,8 A                                                |
| Electrical resistance line constant wire          | 57 Ω/km @ 20 °C                                      |
| Electrical resistance coating wire (Power)        | 26 Ω/km @20 °C                                       |
| AC withstand voltage (wire - wire)                | 2 kV @ 60 s                                          |
| Power frequency withstand voltage (wire - jacket) | 2 kV @ 60 s                                          |
| Min. operating temperature (static)               | -30 °C                                               |
| Max. operating temperature (fixed)                | 80 °C                                                |
| Operating temperature min. (dynamic)              | -5 °C                                                |
| Operating temperature max. (dynamic)              | 70 °C                                                |
| Flame resistance                                  | UL 1581 § 1090   UL 1581 § 1100 FT2   IEC 60332-2-2  |
| chemical resistance                               | Good, application-related testing                    |
| Gasoline resistance                               | Good, application-related testing                    |
| Oil resistance                                    | Good, application-related testing   DIN EN 60811-404 |
| Bending radius (fixed)                            | 5 x Outer diameter                                   |
| Bending radius (dynamic)                          | 10 x Outer diameter                                  |
| Travel speed (C-track)                            | 2 Mio. @ 25 °C                                       |

**Connection type 2**

|                          |                |
|--------------------------|----------------|
| Family construction form | free cable end |
| No. of poles             | 21             |
| Family construction form | M12            |

|                       |        |
|-----------------------|--------|
| Gender                | female |
| Color contact carrier | black  |
| Coding                | A      |
| No. of poles          | 5      |
| PIN 1                 | +      |
| PIN 2                 | NC S 2 |
| PIN 3                 | -      |
| PIN 4                 | NO S 1 |
| PIN 5                 | PE     |