



MET SINGLE-PHASE CONTROL AND ISOLATION TRANSFORMER

P:1500VA IN:400VAC±5% OUT:110VAC

Single-phase - Control and Isolation Transformers
1500 VA
Isolation class T 60/B
Condensation not permitted

[Länk till produkt](#)

Illustration



Produkten kan skilja sig från bilden

Kommersiella uppgifter

ECLASS-6.0	27031202
ECLASS-7.0	27031202
ECLASS-8.0	27031202
ECLASS-9.0	27031202
ETIM-5.0	EC002485
Förpackningsenhet	1
GTIN	4048879073868
Kundens tullnummer	85043200

Electrical data | Supply

Power frequency	50 ... 60 Hz
-----------------	--------------

Electrical data | Input

Input voltage AC	400 V
Input voltage AC min.	380 V
Input voltage AC max.	420 V
Current input AC	4 A
Max. inrush current	85 A
Short-circuit current	120 A

Electrical data | Output

Output voltage AC 1	110 V
Output voltage adjustable	no
Power rating AC max.	1500 VA

Device protection | Electrical

Insulation test voltage input - output	5,8 kV
--	--------

Mechanical data | Mounting data

Mounting method	screwed
Mounting dimension a	135 mm
Mounting dimension b	142 mm
Mounting dimension c	7 mm
Height	142 mm
Width	174 mm
Depth	167 mm
Diameter bore	7 mm
Length bore	15 mm

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
Operating temperature max.	60 °C

Conformity

Product standard	EN 61558-1, EN 61558-2-4, EN 62041 category 0
------------------	---