

## Cube67 Valve-Interface, I/O Extension Module

DO16, MAC Valves, Sub-D 25 pol., 0,5m

Expansion module

DO16 - Valve (E) 0.5 m

Multipole plug (0.5 A)


MAC Valves

Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

### Länk till produkt

#### Illustration



Produkten kan skilja sig från bilden



#### Kommersiella uppgifter

|                    |               |
|--------------------|---------------|
| ECLASS-6.0         | 27242604      |
| ECLASS-6.1         | 27242604      |
| ECLASS-7.0         | 27242604      |
| ECLASS-8.0         | 27242604      |
| ECLASS-9.0         | 27242604      |
| ECLASS-10.1        | 27242604      |
| ECLASS-11.1        | 27242604      |
| ECLASS-12.0        | 27242604      |
| ETIM-5.0           | EC001599      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879045148 |
| Kundens tullnummer | 85389099      |

#### Electrical data | Supply

|                          |            |
|--------------------------|------------|
| Norm operating voltage   | EN 61131-2 |
| Operating voltage UA DC  | 24 V       |
| Current consumption max. | 50 mA      |
| Total current max.       | 4 A        |
| Total current UA max.    | 4 A        |
| Total current US max.    | 4 A        |

**Electrical data | Output**

|                             |       |
|-----------------------------|-------|
| Overload resistant          | yes   |
| Short-circuit protected     | yes   |
| Output current per pin max. | 0,5 A |

**Diagnostics**

|                         |                                  |
|-------------------------|----------------------------------|
| Actuator warning        | per channel via LED and BUS      |
| Diagnostic              | No voltage, Under voltage        |
| Diagnostic via BUS      | per module and channel           |
| Diagnostic via LED      | per module and channel           |
| Short circuit diagnosis | yes                              |
| LED display             | Ethernet connection/data traffic |
| Overload diagnosis      | yes                              |

**Device protection | Electrical**

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP67 |
|-------------------------------------|------|

**Mechanical data | Mounting data**

|                            |                       |
|----------------------------|-----------------------|
| Suitable for mounting type | 2-hole screw mounting |
| Height                     | 150 mm                |
| Width                      | 30 mm                 |
| Depth                      | 34,5 mm               |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | 0 °C   |
| Operating temperature max. | 55 °C  |
| Storage temperature min.   | -20 °C |
| Storage temperature max.   | 75 °C  |

**Connection type 3**

|                          |              |
|--------------------------|--------------|
| Connection type 1        | Bus In       |
| Connection type 2        | Bus Out      |
| Connection type 3        | Data         |
| Family construction form | M12          |
| Gender                   | male         |
| Color contact carrier    | black        |
| Coding                   | A            |
| No. of poles             | 6            |
| PIN 1                    | 24 V DC (UA) |
| PIN 2                    | 24 V DC (US) |
| PIN 3                    | 0 V          |
| PIN 4                    | Bus internal |
| PIN 5                    | Bus internal |
| PIN 6                    | 0 V          |
| Family construction form | M12          |
| Gender                   | female       |
| Color contact carrier    | black        |
| Coding                   | A            |
| No. of poles             | 6            |
| PIN 1                    | 24 V DC (UA) |
| PIN 2                    | 24 V DC (US) |
| PIN 3                    | 0 V          |
| PIN 4                    | Bus internal |
| PIN 5                    | Bus internal |
| PIN 6                    | 0 V          |
| Family construction form | D-Sub        |
| Gender                   | male         |

|              |        |
|--------------|--------|
| No. of poles | 25     |
| PIN 1        | Out 1  |
| PIN 2        | Out 2  |
| PIN 3        | Out 3  |
| PIN 4        | Out 4  |
| PIN 5        | Out 5  |
| PIN 6        | Out 6  |
| PIN 7        | Out 7  |
| PIN 8        | Out 8  |
| PIN 9        | Out 9  |
| PIN 10       | Out 10 |
| PIN 11       | Out 11 |
| PIN 12       | Out 12 |
| PIN 13       | Out 13 |
| PIN 14       | Out 14 |
| PIN 15       | Out 15 |
| PIN 16       | Out 16 |
| PIN 21       | Sens   |
| PIN 22       | 0 V    |
| PIN 23       | 0 V    |
| PIN 24       | 0 V    |
| PIN 25       | 0 V    |