

**MODLINK MSDD DATA INSERT**

1×SUB-D9fem./fem.+1×SUB-D9male/male+1×RJ45+1×USB-A

RJ45; USB (A); SUB-D9; SUB-D9

1× RJ45, 8-pole metal, CAT5e (female/female)

1× USB 2.0 (female/female) form A

1× SUB-D9 (female/female)

1× SUB-D9 (male/male)

**Länk till produkt****Illustration**

Produkten kan skilja sig från bilden

**Kommersiella uppgifter**

|                    |               |
|--------------------|---------------|
| ECLASS-6.0         | 27189217      |
| ECLASS-6.1         | 27189217      |
| ECLASS-7.0         | 27189217      |
| ECLASS-8.0         | 27189217      |
| ECLASS-9.0         | 27189217      |
| ECLASS-10.1        | 27182806      |
| ECLASS-11.1        | 27182806      |
| ECLASS-12.0        | 27182806      |
| ETIM-5.0           | EC002625      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879037631 |
| Kundens tullnummer | 85366990      |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 88 mm |
| Width  | 51 mm |
| Depth  | 45 mm |

**Environmental characteristics | Climatic**

|                          |        |
|--------------------------|--------|
| Storage temperature min. | -30 °C |
| Storage temperature max. | 60 °C  |

| Shielding plate                       |                                                |
|---------------------------------------|------------------------------------------------|
| Connection information                | Threaded hole M4                               |
| Tightening torque                     | 0,9 Nm                                         |
| USB                                   |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage DC (UL-listed)      | 42,4 V                                         |
| Operating current max.                | 500 mA                                         |
| USB specification                     | 2.0                                            |
| Data transmission rate max.           | 480 MBit/s                                     |
| Looking techniques                    | Snap-in connector                              |
| SUB-D9                                |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | male                                           |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |
| RJ45                                  |                                                |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | RJ45                                           |
| Family type Back side                 | RJ45                                           |
| Cable category min.                   | Cat5e                                          |
| Looking techniques                    | Snap-in connector                              |