

Signal tower Modlight70 Pro equipped with LED modules


green,amber,red,M12 plug side

Basic + LED modules + M12 (side)

green, yellow, red

[Länk till produkt](#)**Illustration**

Produkten kan skilja sig från bilden



Male

PIN 1: +
 PIN 2: LED (red)
 PIN 3: –
 PIN 4: LED (clear)
 PIN 5: LED (yellow)
 PIN 6: LED (blue)
 PIN 7: LED (green)
 PIN 8: Continuous alarm

**Kommersiella uppgifter**

ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
Förpackningsenhet	1
GTIN	4048879759946
Kundens tullnummer	85318070

Electrical data | Supply

Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V
Current consumption max.	135 mA

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked

Mechanical data | Material data

Color housing	black
---------------	-------

Material housing Plastic

Mechanical data | Mounting data

Height	293 mm
Width	70 mm
Depth	70 mm

Environmental characteristics | Climatic

Operating temperature min.	-30 °C
Operating temperature max.	60 °C