

M12 male 0° B-cod. screw terminal shielded

5-pol., max. 0.75mm², 4 - 6mm, shielded

PROFIBUS

Male straight

M12, 5-pole

B-coded



shielded

Screw terminals

Sealing range (cable Ø): 4...6 mm

Länk till produkt

Illustration



Produkten kan skilja sig från bilden

Side 1

Family construction form	M12
Degree of protection (EN IEC 60529)	IP67

Kommersiella uppgifter

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102

ECLASS-10.1	27440102
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ETIM-5.0	EC002635
Förpackningsenhet	1
GTIN	4048879622851
Kundens tullnummer	85366990

Electrical data | Supply

Operating voltage AC max.	60 V
Operating voltage DC max.	60 V
Current operating per contact max.	4 A

Installation

Connection cross section max.	0,75 mm ²
-------------------------------	----------------------

Device protection | Electrical

Additional condition protection degree	inserted, screwed
--	-------------------

Mechanical data | Material data

Coating housing	nickel plated
Material housing	Brass

Mechanical data | Mounting data

Clamping range min.	4 mm
Clamping range max.	6 mm

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
Operating temperature max.	85 °C