MURR ELEKTRONIK
stay connected

M12 female 90° B-cod. screw terminal shielded


5-pol., max. 0.75mm², 6 - 8mm, shielded


PROFIBUS, Interbus
Female 90°
M12, 5-pole
B-coded
shielded
Screw terminals
Sealing range (cable Ø): 6...8 mm


Länk till produkt

Illustration









Produkten kan skilja sig från bilden

Side 1	
Family construction form	M12
Degree of protection (EN IEC 60529)	IP67

Kommersiella uppgifter	
ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102

MURR ELEKTRONIK
stay connected

ECLASS-10.1	27440102
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ETIM-5.0	EC002635
Förpackningsenhet	1
GTIN	4048879198608
Kundens tullnummer	85366990
Electrical data | Supply	
Operating voltage AC max.	60 V
Operating voltage DC max.	60 V
Current operating per contact max.	4 A
Installation	
Connection cross section max.	0,75 mm²
Device protection | Electrical	
Additional condition protection degree	inserted, screwed
Mechanical data | Material data	
Coating housing	nickel plated
Material housing	Brass
Mechanical data | Mounting data	
Clamping range min.	6 mm
Clamping range max.	8 mm
Environmental characteristics | Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	85 °C