

## Pneumatic insert - male, 6 mm

Pneumatic male

Internal hose Ø

6 mm

Technical data will be only guaranteed with Murrelektronik components.

### [Länk till produkt](#)

#### Illustration



Produkten kan skilja sig från bilden

#### Kommersiella uppgifter

|                    |               |
|--------------------|---------------|
| ECLASS-6.0         | 27261204      |
| ECLASS-6.1         | 27261290      |
| ECLASS-7.0         | 27440290      |
| ECLASS-8.0         | 27440290      |
| ECLASS-9.0         | 27440220      |
| ECLASS-10.1        | 27440220      |
| ECLASS-11.1        | 27440220      |
| ECLASS-12.0        | 27440220      |
| ETIM-5.0           | EC000438      |
| Förpackningsenhet  | 10            |
| GTIN               | 4048879672771 |
| Kundens tullnummer | 39269097      |

#### Installation | Connection

|                    |      |
|--------------------|------|
| Gender             | male |
| Mating cycles min. | 500  |

#### Mechanical data

|                         |       |
|-------------------------|-------|
| Operating pressure max. | 8 bar |
| Integrated valve        | no    |

#### Mechanical data | Material data

|                  |               |
|------------------|---------------|
| Material housing | Delrin Acetal |
|------------------|---------------|

#### Mechanical data | Mounting data

|                 |      |
|-----------------|------|
| Internal hose Ø | 6 mm |
|-----------------|------|

#### Environmental characteristics | Climatic

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -40 °C |
| Operating temperature max. | 80 °C  |

