

Push Pull Power / Push Pull Power

PUR 5x1.5 gy UL/CSA+drag chain 10m

Customized printing and packaging

Male

RJ45PP – RJ45PP

5-pole





Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

Länk till produkt

Illustration



Produkten kan skilja sig från bilden



Cable length 10 m

Side 1

Mounting method inserted, screwed

|                                                 |                                                                                                                           |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Family construction form                        | M12P                                                                                                                      |
| Material contact                                | Copper alloy                                                                                                              |
| No. of poles                                    | 5                                                                                                                         |
| <b>Side 2</b>                                   |                                                                                                                           |
| Mounting method                                 | inserted, screwed                                                                                                         |
| Family construction form                        | Push Pull                                                                                                                 |
| Material contact                                | Copper alloy                                                                                                              |
| No. of poles                                    | 5                                                                                                                         |
| <b>Kommersiella uppgifter</b>                   |                                                                                                                           |
| ECLASS-6.0                                      | 27279218                                                                                                                  |
| ECLASS-7.0                                      | 27279218                                                                                                                  |
| ECLASS-8.0                                      | 27279218                                                                                                                  |
| ECLASS-9.0                                      | 27060311                                                                                                                  |
| ECLASS-10.1                                     | 27060311                                                                                                                  |
| ECLASS-11.1                                     | 27060311                                                                                                                  |
| ECLASS-12.0                                     | 27060327                                                                                                                  |
| ETIM-5.0                                        | EC001855                                                                                                                  |
| Förpackningsenhet                               | 1                                                                                                                         |
| GTIN                                            | 4048879839549                                                                                                             |
| Kundens tullnummer                              | 85444210                                                                                                                  |
| <b>Electrical data   Supply</b>                 |                                                                                                                           |
| Operating voltage AC max.                       | 24 V                                                                                                                      |
| Operating voltage DC max.                       | 24 V                                                                                                                      |
| Current operating per contact max.              | 16 A                                                                                                                      |
| <b>Diagnostics</b>                              |                                                                                                                           |
| Status indication LED                           | no                                                                                                                        |
| <b>Device protection   Electrical</b>           |                                                                                                                           |
| Degree of protection (EN IEC 60529)             | IP65, IP67                                                                                                                |
| Additional condition protection degree          | inserted, locked                                                                                                          |
| Pollution Degree                                | 2                                                                                                                         |
| Rated surge voltage                             | 4 kV                                                                                                                      |
| <b>Mechanical data   Material data</b>          |                                                                                                                           |
| Coating housing                                 | nickel plated                                                                                                             |
| Material housing                                | Zinc die-casting                                                                                                          |
| <b>Mechanical data   Mounting data</b>          |                                                                                                                           |
| Looking techniques                              | Push Pull Power                                                                                                           |
| <b>Environmental characteristics   Climatic</b> |                                                                                                                           |
| Operating temperature min.                      | -40 °C                                                                                                                    |
| Operating temperature max.                      | 85 °C                                                                                                                     |
| Additional condition temperature range          | depending on cable quality                                                                                                |
| <b>Installation   Cable</b>                     |                                                                                                                           |
| Cable identification                            | P08                                                                                                                       |
| Cable Type                                      | 3                                                                                                                         |
| Printing color of wire insulation               | black (pink isolation), black (white isolation), white (isolation blue), white (isolation brown), white (isolation black) |
| Jacket Color                                    | gray                                                                                                                      |
| Type of Certificate                             | cURus                                                                                                                     |
| Amount stranding                                | 1                                                                                                                         |
| Stranding                                       | 5 wires around Filler twisted                                                                                             |
| Filler                                          | yes                                                                                                                       |
| wire arrangement                                | pink 5, black 4, blue 3, white 2, brown 1                                                                                 |
| Material jacket                                 | PUR                                                                                                                       |

|                                                   |                                                                                                                           |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Shore hardness jacket                             | 90 ± 5 Shore A                                                                                                            |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                                            |
| Outer-diameter (jacket)                           | 8,2 mm                                                                                                                    |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                                                                                     |
| Material wire insulation                          | PP                                                                                                                        |
| Amount wires                                      | 5                                                                                                                         |
| Outer diameter insulation                         | 2,3 mm                                                                                                                    |
| Outer diameter tolerance core insulation          | ± 5 %                                                                                                                     |
| Shore hardness wire insulation                    | 60 ± 5 Shore D                                                                                                            |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                                            |
| Printing color of wire insulation                 | black (pink isolation), black (white isolation), white (isolation blue), white (isolation brown), white (isolation black) |
| Amount strands (wire)                             | 84                                                                                                                        |
| Diameter of single wires                          | 0,15 mm                                                                                                                   |
| Conductor crosssection (wire)                     | 1,5 mm <sup>2</sup>                                                                                                       |
| Material conductor wire                           | Stranded copper wire, bare                                                                                                |
| Conductor type (wire)                             | strand class 6                                                                                                            |
| Traversing distance (C-track)                     | 5 m @ 25 °C                                                                                                               |
| Nominal voltage AC max.                           | 1000 V                                                                                                                    |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                                                                                         |
| Current load capacity min. wire                   | 13,5 A                                                                                                                    |
| Electrical resistance line constant wire          | 13,3 Ω/km @ 20 °C                                                                                                         |
| AC withstand voltage (wire - wire)                | 10 kV @ 60 s                                                                                                              |
| Power frequency withstand voltage (wire - jacket) | 10 kV @ 60 s                                                                                                              |
| Min. operating temperature (static)               | -50 °C                                                                                                                    |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                                                                                         |
| Operating temperature min. (dynamic)              | -25 °C                                                                                                                    |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                                                                                         |
| Flame resistance                                  | UL 1581 § 1100 FT2   UL 1581 § 1090   IEC 60332-2-2                                                                       |
| chemical resistance                               | Good, application-related testing                                                                                         |
| Gasoline resistance                               | Good, application-related testing                                                                                         |
| Oil resistance                                    | DIN EN 60811-404   Good, application-related testing                                                                      |
| Bending radius (installation)                     | x Outer diameter                                                                                                          |
| Bending radius (fixed)                            | 7,5 x Outer diameter                                                                                                      |
| Bending radius (dynamic)                          | 10 x Outer diameter                                                                                                       |
| Travel speed (C-track)                            | 5 Mio. @ 25 °C                                                                                                            |
| No. of torsion cycles                             | 2 Mio.                                                                                                                    |
| Torsion stress                                    | ± 180 °/m                                                                                                                 |
| Torsion speed                                     | 35 cycles/min                                                                                                             |