

**EXACT12, 4XM12, 5-POLE, BASIC HOUSING, W.O. LED'S**

Without homerun-cable

4-way, 5-pole



without LED, up to 125 V AC/DC

Screw plug-in terminals


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

**Länk till produkt****Illustration**

Produkten kan skilja sig från bilden

**Kommersiella uppgifter**

|            |          |
|------------|----------|
| ECLASS-6.0 | 27279219 |
| ECLASS-6.1 | 27279219 |
| ECLASS-7.0 | 27279219 |

|                    |               |
|--------------------|---------------|
| ECLASS-8.0         | 27279219      |
| ECLASS-9.0         | 27440108      |
| ECLASS-10.1        | 27440111      |
| ECLASS-11.1        | 27440111      |
| ECLASS-12.0        | 27440111      |
| ETIM-5.0           | EC002585      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879055833 |
| Kundens tullnummer | 85369010      |

**Electrical data | Supply**

|                                    |       |
|------------------------------------|-------|
| Operating voltage AC               | 125 V |
| Operating voltage DC               | 125 V |
| Current operating per contact max. | 4 A   |
| Total current max.                 | 8 A   |

**Device protection | Electrical**

|                                     |            |
|-------------------------------------|------------|
| Degree of protection (EN IEC 60529) | IP65, IP67 |
|-------------------------------------|------------|

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C  |

**Connection type 2**

|                          |        |
|--------------------------|--------|
| Family construction form | Cap    |
| No. of poles             | 16     |
| Family construction form | M12    |
| Gender                   | female |
| Color contact carrier    | black  |
| Coding                   | A      |
| No. of poles             | 5      |
| PIN 1                    | +      |
| PIN 2                    | NC S 2 |
| PIN 3                    | -      |
| PIN 4                    | NO S 1 |
| PIN 5                    | PE     |