

**MODL. VARIO 8-way fixed housing type B**

nickel plated aluminum

Stationary housing (round)

Aluminium

8-way

**[Länk till produkt](#)****Illustration**

Produkten kan skilja sig från bilden

**Kommersiella uppgifter**

|                    |               |
|--------------------|---------------|
| ECLASS-6.0         | 27260702      |
| ECLASS-6.1         | 27260708      |
| ECLASS-7.0         | 27440312      |
| ECLASS-8.0         | 27440312      |
| ECLASS-9.0         | 27440312      |
| ECLASS-10.1        | 27440312      |
| ECLASS-11.1        | 27440312      |
| ECLASS-12.0        | 27440312      |
| ETIM-5.0           | EC002641      |
| Förpackningsenhet  | 1             |
| GTIN               | 4048879573023 |
| Kundens tullnummer | 85389099      |

**Device protection | Electrical**

|                                        |                   |
|----------------------------------------|-------------------|
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68  |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K      |
| Additional condition protection degree | inserted, screwed |

**Mechanical data**

|                         |          |
|-------------------------|----------|
| Operating pressure min. | -0,8 bar |
| Operating pressure max. | 16 bar   |

**Mechanical data | Material data**

|                  |                      |
|------------------|----------------------|
| Coating housing  | powder-coated        |
| Material housing | Aluminum die casting |

**Mechanical data | Mounting data**

|                 |              |
|-----------------|--------------|
| Mounting method | screw fixing |
|-----------------|--------------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 120 °C |