

MODL. VARIO insert for fixed housing type B

4/2 no shut-off, dezincification resistant brass

Modlink Vario
 Insert - stationary housing
 Brass, dezincification-resistant
 without shut-off
 AD4

Länk till produkt**Illustration**

Produkten kan skilja sig från bilden

Kommersiella uppgifter

ECLASS-6.0	27260702
ECLASS-6.1	27260708
ECLASS-7.0	27440312
ECLASS-8.0	27440312
ECLASS-9.0	27440312
ECLASS-10.1	27440312
ECLASS-11.1	27440312
ECLASS-12.0	27440312
ETIM-5.0	EC002641
Förpackningsenhet	1
GTIN	4048879572514
Kundens tullnummer	74198090

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65, IP67, IP68
Degree of protection (ISO 20653:2013)	IP66K, IP69K
Additional condition protection degree	inserted, screwed

Mechanical data

Barrier	without shut-off
Operating pressure min.	-0,8 bar
Operating pressure max.	16 bar

Mechanical data | Material data

Material gasket	FPM
Material housing	Brass

Mechanical data | Mounting data

Outer diameter hose	4 mm
---------------------	------

Environmental characteristics Climatic	
---	--

Operating temperature min.	-20 °C
Operating temperature max.	120 °C
